



11636 GOLDRING RD • ARCADIA, CALIFORNIA 91006-5815
626-358-2559 • FAX 626-359-5701 • 800-525-6925

INSTRUCTIONS
TMP-646 Telephone Transmit & Receive Patch
For Use With Sound Card or Tape Recorder
P/N 43933

The TMP-646 Telephone Transmit & Receive Patch allows you to record and play back to your telephone from your sound card or tape recorder.

- Record telephone conversations
- Record just your voice through your sound card (i.e. memos, repetitive, canned announcements...)
- Playback from your sound card over the phone (announcements, music, phone conversations, etc.)

Installation is easy, and operation is automatic, with no switches. The TMP-646 is compatible with analog and digital phones, and standard sound cards and tape recorders. You can leave it connected to your phone since it does not interfere with normal telephone operation. Will not record speakerphone.

The operation of the TMP-646 is completely automatic. Simply install it according to the instructions below and operate your sound card controls as usual. Note: Make sure the "Monitor" switch on your sound card software (if any) is set to OFF to avoid feedback. Playback can be heard in your earphone and on the other end of the call.

To Install: (See diagram)

- 1 Unplug headset (or handset) coil cord from the base of the telephone, and plug the short modular cord from TMP-646 in its place.
- 2 Plug the headset coil cord into the modular jack on the TMP-646.
- 3 Insert the 3.5mm GREEN plug on the long cord into the speaker or headphone jack on the sound card or recorder.
- 4 Insert the 3.5mm PINK plug on the long cord into the MIC jack on the sound card or recorder.
- 5 Make sure "Monitor" switch (if any) in sound card software is set to OFF.
- 6 Operate your sound card and phone according to the applicable hardware and software instructions for your system.

INSTRUCTIONS
TMP-646 Telephone Transmit & Receive Patch
For Use With Sound Card or Tape Recorder
P/N 43933

